























Container	Description	Configuration Temp (°C)	Performance in hours at 30°C	External Dims (mm)	Payload Dims (mm)	Payload Volume (litres)	Tare Weight (kg)	Volumetric (kg) (6000cc)
 KTEvolution26 T KTEvolution26 R KTEvolution26 F KTEvolution26 D	Hand-held container is a manually handleable by two persons, weatherproof, and washable supply chain solution.	+15 to +25 +2 to +8 -25 to -15 <-60	120+	(LWH) 443 x 403 x 545 443 x 403 x 545 443 x 403 x 545 443 x 403 x 545	(LWH) 300 x 260 x 340 300 x 260 x 340 300 x 260 x 340 300 x 260 x 340	26.5	29 21.5 26 21.5	16.2
 KTEvolution57 T KTEvolution57 R KTEvolution57 F KTEvolution57 D	Hand-held container is a manually handleable by two persons, weatherproof, and washable supply chain solution.	+15 to +25 +2 to +8 -25 to -15 <-60	120+	703 x 443 x 545 703 x 443 x 545 703 x 443 x 545 703 x 443 x 545	560 x 300 x 340 560 x 300 x 340 560 x 300 x 340 560 x 300 x 340	57.1	46 33 41 31	28.3
 KT400 T KT400 R-S KT400 F	Sub-pallet payload for narrow-bodied aircraft and light goods vehicles. KT400R-H specially designed for extreme conditions	+15 to +25 +2 to +8 -25 to -15	120+ 120+ 120+	1200 x 800 x 1050 1200 x 800 x 1050 1200 x 800 x 1050	900 x 500 x 585 900 x 500 x 585 900 x 500 x 585	263 263 263	248 188 220	168 168 168
 KT400 D	Sub-pallet, ultra-cold payload for narrow-bodied aircraft and light goods vehicles	-80 to -60 -80 to -60 -80 to -60	120+ 120+ 120+	1200 x 800 x 1050 1200 x 800 x 1050 1200 x 800 x 1050 1200 x 800 x 1050	1020 x 610 x 750* 789 x 522 x 509 885 x 460 x 595 705 x 454 x 588	466* 209 242 188	70* 226 (based on 127 packout) 214 (based on 157 packout) 228 (based on 025 packout)	168 168 168 168
 KTM21 T KTM21 R KTM21 F	"Low" Euro pallet payload, for narrow-bodied aircraft and light goods vehicles	+15 to +25 +2 to +8 -25 to -15	120+ 120+ 120+	1550 x 1130 x 930 1550 x 1130 x 930 1550 x 1130 x 930	1250 x 820 x 550 1250 x 820 x 550 1250 x 820 x 550	564 564 564	322 269 305	271 271 271
 KTM31 T KTM31 R KTM31 F	"Low" US pallet payload, for narrow-bodied aircraft and light goods vehicles	+15 to +25 +2 to +8 -25 to -15	120+ 120+ 120+	1550 x 1540 x 930 1550 x 1540 x 930 1550 x 1540 x 930	1250 x 1230 x 550 1250 x 1230 x 550 1250 x 1230 x 550	846 846 846	415 344 393	370 370 370
 KTM22 T KTM22 R KTM22 F	Single Euro pallet payload for wide-bodied aircraft and light goods vehicles	+15 to +25 +2 to +8 -25 to -15	120+ 120+ 120+	1550 x 1130 x 1580 1550 x 1130 x 1580 1550 x 1130 x 1580	1250 x 820 x 1200 1250 x 820 x 1200 1250 x 820 x 1200	1230 1230 1230	483 400 457	461 461 461
 KTM32 T KTM32 R KTM32 F	Single US pallet payload for wide-bodied aircraft and pallet vehicles	+15 to +25 +2 to +8 -25 to -15	120+ 120+ 120+	1550 x 1540 x 1580 1550 x 1540 x 1580 1550 x 1540 x 1580	1250 x 1230 x 1200 1250 x 1230 x 1200 1250 x 1230 x 1200	1845 1845 1845	609 503 576	629 629 629
 KTM42 T KTM42 R KTM42 F	Double Euro pallet payload for wide-bodied aircraft and pallet vehicles	+15 to +25 +2 to +8 -25 to -15	120+ 120+ 120+	1550 x 1950 x 1580 1550 x 1950 x 1580 1550 x 1950 x 1580	1250 x 1640 x 1200 1250 x 1640 x 1200 1250 x 1640 x 1200	2460 2460 2460	751 621 710	796 796 796
 KTM42 D	Ultra Cold, Double Euro pallet payload for wide-bodied aircraft and pallet vehicles	-80 to -60	120+ in a constant refrigerated environment	1550 x 1950 x 1580	1250 x 1640 x 1050	2153	617 417*	796
 KTM52 T KTM52 R KTM52 F	Double US pallet payload for wide-bodied aircraft and pallet vehicles	+15 to +25 +2 to +8 -25 to -15	120+ 120+ 120+	1550 x 2360 x 1580 1550 x 2360 x 1580 1550 x 2360 x 1580	1250 x 2050 x 1200 1250 x 2050 x 1200 1250 x 2050 x 1200	3075 3075 3075	888 734 840	963 963 963

Container	Description	Configuration Temp (°F)	Performance in hours at 86°F	External Dims (inches)	Payload Dims (inches)	Payload Volume (cubic feet)	Tare Weight (lbs)	Volumetric (lbs) (6000cc)
 KTEvolution26 T KTEvolution26 R KTEvolution26 F KTEvolution26 D	Hand-held container is a manually handleable by two persons, weatherproof, and washable supply chain solution.	+59 to +77 +35 to +46 -13 to +5 <-76	120+	(LWH) 17.4 x 15.8 x 21.4 17.4 x 15.8 x 21.4 17.4 x 15.8 x 21.4 17.4 x 15.8 x 21.4	(LWH) 11.8 x 10.2 x 13.4 11.8 x 10.2 x 13.4 11.8 x 10.2 x 13.4 11.8 x 10.2 x 13.4	0.9	70 48 57 47	36
 KTEvolution57 T KTEvolution57 R KTEvolution57 F KTEvolution57 D	Hand-held container is a manually handleable by two persons, weatherproof, and washable supply chain solution.	+59 to +77 +35 to +46 -13 to +5 <-76	120+	27.6 x 17.4 x 21.4 27.6 x 17.4 x 21.4 27.6 x 17.4 x 21.4 27.6 x 17.4 x 21.4	22 x 11.8 x 13.4 22 x 11.8 x 13.4 22 x 11.8 x 13.4 22 x 11.8 x 13.4	2.0	101 73 90 68	62
 KT400 T KT400 R-S KT400 F	Sub-pallet payload for narrow-bodied aircraft and light goods vehicles. KT400R-H specially designed for extreme conditions	+59 to +77 +35 to +46 -13 to +5	120+ 120+ 120+	31.5 x 47.2 x 41.3 31.5 x 47.2 x 41.3 31.5 x 47.2 x 41.3	19.7 x 35.4 x 23 19.7 x 35.4 x 23 19.7 x 35.4 x 23	9.3 9.3 9.3	547 414 485	370 370 370
 KT400 D	Sub-pallet, ultra-cold payload for narrow-bodied aircraft and light goods vehicles	-112 to -76 -112 to -76 -112 to -76	120+ 120+ 120+	31.5 x 47.2 x 41.3 31.5 x 47.2 x 41.3 31.5 x 47.2 x 41.3	21.1 x 37.3 x 23* 31.0 x 20.5 x 20.0 34.8 x 18.1 x 23.4 27.7 x 17.8 x 23.1	16.5 7.4 8.5 6.6	154* 498 (based on 127 packout) 471 (based on 157 packout) 503 (based on 025 packout)	370
 KTM21 T KTM21 R KTM21 F	"Low" Euro pallet payload, for narrow-bodied aircraft and light goods vehicles	+59 to +77 +35 to +46 -13 to +5	120+ 120+ 120+	44.5 x 61 x 36.6 44.5 x 61 x 36.6 44.5 x 61 x 36.6	32.3 x 49.2 x 21.6 32.3 x 49.2 x 21.6 32.3 x 49.2 x 21.6	19.9 19.9 19.9	710 593 672	597 597 597
 KTM31 T KTM31 R KTM31 F	"Low" US pallet payload, for narrow-bodied aircraft and light goods vehicles	+59 to +77 +35 to +46 -13 to +5	120+ 120+ 120+	60.6 x 61 x 36.6 60.6 x 61 x 36.6 60.6 x 61 x 36.6	48.4 x 49.2 x 21.6 48.4 x 49.2 x 21.6 48.4 x 49.2 x 21.6	29.9 29.9 29.9	915 758 866	816 816 816
 KTM22 T KTM22 R KTM22 F	Single Euro pallet payload for wide-bodied aircraft and light goods vehicles	+59 to +77 +35 to +46 -13 to +5	120+ 120+ 120+	44.5 x 61 x 62.2 44.5 x 61 x 62.2 44.5 x 61 x 62.2	32.3 x 49.2 x 47.2 32.3 x 49.2 x 47.2 32.3 x 49.2 x 47.2	43.4 43.4 43.4	1065 882 608	1016 1016 1016
 KTM32 T KTM32 R KTM32 F	Single US pallet payload for wide-bodied aircraft and pallet vehicles	+59 to +77 +35 to +46 -13 to +5	120+ 120+ 120+	60.6 x 61 x 62.2 60.6 x 61 x 62.2 60.6 x 61 x 62.2	48.4 x 49.2 x 47.2 48.4 x 49.2 x 47.2 48.4 x 49.2 x 47.2	65.1 65.1 65.1	1343 1109 1270	1387 1387 1387
 KTM42 T KTM42 R KTM42 F	Double Euro pallet payload for wide-bodied aircraft and pallet vehicles	+59 to +77 +35 to +46 -13 to +5	120+ 120+ 120+	76.8 x 61 x 62.2 76.8 x 61 x 62.2 76.8 x 61 x 62.2	64.5 x 49.2 x 47.2 64.5 x 49.2 x 47.2 64.5 x 49.2 x 47.2	86.9 86.9 86.9	1656 1369 1565	1755 1755 1755
 KTM42 D	Ultra Cold, Double Euro pallet payload for wide-bodied aircraft and pallet vehicles	-112 to -76	120+ in a constant refrigerated environment	76.8 x 61 x 62.2	64.5 x 49.2 x 41.3	76	1360 919*	1755
 KTM52 T KTM52 R KTM52 F	Double US pallet payload for wide-bodied aircraft and pallet vehicles	+59 to +77 +35 to +46 -13 to +5	120+ 120+ 120+	92.9 x 61 x 62.2 92.9 x 61 x 62.2 92.9 x 61 x 62.2	80.7 x 49.2 x 47.2 80.7 x 49.2 x 47.2 80.7 x 49.2 x 47.2	108.6 108.6 108.6	1958 1618 1852	2123 2123 2123